



## General info

### Indoor - Suspensions

Indoor suspended lamp with multiple integrated LED sources and direct light emission

|                     |                        |
|---------------------|------------------------|
| <b>Ean</b>          | 8021696247281          |
| <b>Item</b>         | GEMINI SP D081 NERO    |
| <b>Installation</b> | Suspension             |
| <b>Guarantee</b>    | 5 years                |
| <b>Gross weight</b> | 4.75 kg                |
| <b>Volume</b>       | 0.07744 m <sup>3</sup> |

## Technical info

|                              |  |
|------------------------------|--|
| <b>Net weight</b>            | 2.06 kg  |
| <b>Insulation class</b>      | I  |
| <b>Protection index</b>      | IP20   |
| <b>Compliance</b>            | CE   |
| <b>Operating temperature</b> | 0° ~ +40 °C  |
| <b>Dimmer</b>                | Non-dimmable, On-Off   |
| <b>Power output</b>          | 220-240 V AC 50/60 Hz  |
| <b>Power supply</b>          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

## Source info

|                               |   |
|-------------------------------|---|
| <b>Integrated source</b>      | Integrated LED module                     |
| <b>Replaceable source</b>     | Replaceable (by qualified operators only) |
| <b>Power</b>                  | LED 60 W                                  |
| <b>Emission</b>               | Direct                                    |
| <b>Max consumption</b>        | max 60,00 W                               |
| <b>Features LED</b>           | LED SMD                                   |
| <b>CCT</b>                    | 3000 K                                    |
| <b>Duration LED (t. 25°C)</b> | 50000 h                                   |
| <b>CRI</b>                    | > 80                                      |
| <b>Light beam</b>             | 130°                                      |
| <b>Light beam flux</b>        | 8100 lm                                   |
| <b>Useful light flux</b>      | 3300 lm                                   |
| <b>Photobiological risk</b>   | 1   |
| <b>Standby power</b>          | < 0.50 W                                  |